

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

October 19, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation W. W. Hamilton Well No. 1 in the _____
 Company or Operator Lease

NE 1/4 SW 1/4 of Sec. 35, T. 16S, R. 38E, N. M. P. M.,
Wildcat Field, Lea County.

The dates of this work were as follows: October 18, 19, 1948

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on October 18, 19 48
 and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

4808' Total Depth, Anhydrite & Lime. Ran Schlumberger Survey and their Gamma Ray from 4808' to top. Ran total of 137 jts. of 8-5/8" OD, 36# & 32#, J-55, R-2 & 3, 8-RT, Reg. & Long T/C, SS Casing New and set at 4806'. Run in the following order: 15 jts. of 36#, R-2, Reg. T/C; 42 jts. of 32#, R-3, Reg. T/C; 1 jt. of 32#, R-2, Reg. T/C; 20 jts. of 32#, R-3, Long T/C and 59 jts. of 32#, R-2, Long T/C. Cemented with 500 sx White Hall Cement mixed 2% Howcogel and 100 sx White Hall Cement for a total of 600 sx and plug pumped to 4741' at 7:00AM, 10-19-48. Final pressure 800#.

Witnessed by K. V. Stephenson Amerada Petroleum Corporation Foreman
 Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

19th. day of October 1948Name Don ToppPosition Asst. Dist. Supt.Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

Ray G. Harkness
 Name
 Title

OCT 21 1948