

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD 9 48

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Carper Drilling Company, Inc.
(Company or Operator)

Taylor
(Lease)

Well No. 3, in SE 1/4 of SW 1/4, of Sec. 30, T. 16 S, R. 32 E, NMPM.

Robinson Pool, Lea County.

Well is 330 feet from South line and 1585 feet from West line

of Section 30. If State Land the Oil and Gas Lease No. is

Drilling Commenced November 1, 1959. Drilling was Completed December 16, 1959.

Name of Drilling Contractor Carper Drilling Company, Inc.

Address Artesia, New Mexico

Elevation above sea level at Top of Tubing Head 4121'. The information given is to be kept confidential until, 19.

OIL SANDS OR ZONES

No. 1, from 3835 to 3850 No. 4, from to
3990 4000
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24	new	943'	Guide			surface
5 1/2	14	"	4021'	"			production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8 5/8	945	50	pump & plug		
8"	5 1/2	4030	100	" "		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Faced with 66,990 gals. refined oil and 47,500 lb. sand

Result of Production Stimulation After recover of load, well pumped 25 BOPD

Depth Cleaned Out 4025'

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 945 feet, and from 945 feet to 4032 feet.
Cable tools were used from 945 feet to 4032 feet, and from 4032 feet to 4032 feet.

PRODUCTION

Put to Producing 4-21-60, 1960
OIL WELL: The production during the first 24 hours was 25 barrels of liquid of which 100% was oil; 35% was emulsion; 0% water; and 0% was sediment. A.P.I. Gravity 35
GAS WELL: The production during the first 24 hours was 0 M.C.F. plus 0 barrels of liquid Hydrocarbon. Shut in Pressure 0 lbs.
Length of Time Shut in 0

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	930		T. Devonian		T. Ojo Alamo
T. Salt	1085		T. Silurian		T. Kirtland-Fruitland
B. Salt	2060		T. Montoya		T. Farmington
T. Yates	2225		T. Simpson		T. Pictured Cliffs
T. 7 Rivers	2710		T. McKee		T. Menefee
T. Queen	3141		T. Ellenburger		T. Point Lookout
T. Grayburg	3501		T. Gr. Wash.		T. Mancos
T. San Andres	3883		T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn.
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn.			T.		T.
T. Miss.			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	930	930	red beds				
930	1085	155	anhyd.				
1085	2060	975	Salt				
2060	2225	165	Anhyd.				
2225	2325	100	Sand				
2325	2885	560	Anhyd., lime				
2885	2900	15	Sand				
2900	3141	241	Anhyd., lime				
3141	3166	15	Sand				
3166	3835	665	Anhyd., lime				
3835	3856	21	Sand				
3856	4032	176	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Carper Drilling Co., Inc. Address Artesia, N. M. (Date) 4-27 1960
Name Luke E. Starn Position or Title Supt. of Prod.