

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029405 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

Box 460, Hobbs, N.M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' S - 860' E Sec. 19

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA UNIT

9. WELL NO.

259

10. FIELD AND POOL, OR WILDCAT

MAL. G-SA REPRESS.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 19, T-17S, R-32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3949' DF

OCT 8 1974
GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) SQUEEZE 9TH MASSIVE

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran cement retainer & set @ 3952'. Pumped 20 sks Class "C" Cement below retainer. Tagged cement @ 3872'. Drilled out cement bridge 3872'-3940'. Pressured up on casing w/1500 p.s.i. Press. dec. to 800 p.s.i. in 14 min & 0 p.s.i. in 35 min. Displaced hole w/ trtd wtr. Spotted 1 1/2 sks Cal-seal on top of retainer. Press. csq w/1000# & S.I. 1 hr. Rel. pressure. No back flow. Well now shut in. Work started 9-5-74, completed 9-11-74.

11-1-75

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

SR. ANALYST

DATE

10-7-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
OCT 10 1974

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

USGS-5, Porters-3, File