

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLIC.  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-0294056

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection  
2. NAME OF OPERATOR Continental Oil Company  
3. ADDRESS OF OPERATOR Box 460 Hobbs, New Mexico  
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

660' FSL and 660' FEL of Sec 19

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3923' df

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit 1

9. WELL NO.

100

10. FIELD AND POOL, OR WILDCAT

Maj G-SA Repair

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 19, T-17S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE N. Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Set OH packer at 3850'. Treated OH 3850'-4040' w/ 1000 gals 28% acid. Set 4 1/2" 9.5# casing at 3575'. Cemented w/ 175 sacks class C cement w/ 4% gel and 3/4 of 1% CFR-2. Followed w/ 100 sacks class C cement w/ 3% salt, 3% sand and 3/4 of 1% CFR-2. Top of cement by survey at 440'.  
Work started - 5-12-72  
Completed - 5-16-72

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Admin. Supervisor

DATE

5-16-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

MAY 17 1972

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side