

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other Instructions on Reverse Side)Form approved
Budget Bureau No. 42-R1474

5. LEASE DESIGNATION AND SERIAL NO.

LC-02940.5 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <i>Injection Well</i>	7. UNIT AGREEMENT NAME <i>McAlister Pipe</i>
2. NAME OF OPERATOR <i>Continental Oil Company</i>	8. FARM OR LEASE NAME <i>McAlister</i>
3. ADDRESS OF OPERATOR <i>P.O. Box 460, Hobbs, N.M.</i>	9. WELL NO. <i>59</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <i>1980' FS+EL of Sec. 19, T-17S, R-32E, Lea County, N.M.</i>	10. FIELD AND POOL, OR WILDCAT <i>McAlister</i>
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, CR, etc.) <i>3938 DF</i>
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>Sec 19 T-17S, R-32E</i>
	12. COUNTY OR PARISH <i>Lea</i>
	13. STATE <i>N.M.</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

Deepen 55' & Stimulate

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to drill w/6 1/4" bit and jet sub 55' to new TD 4040'.
Spot 500 gal 6X-15 PC retarded acid through bit and OH. Let soak for 30-60 min. then squeeze acid away w/50 BW at 1-2 BPM. Re-run cement lined plug + packer & place well back on injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

4568 (3) MCA (3) File

APPROVED

FEB 12 1971

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side