N.M. OIL CONS. COMMISSION P.O. BOX 1980 HOBBS, NEW MEXICO 88240

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED			
Budget Bureau No. 1004-0135			
Expires: March 31, 1993			

DEFARTMENT OF THE INTERIOR		Expires: March 31, 1993
BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS		5. Lease Designation and Serial No.
		LC 029405A
		6. If Indian, Allottee or Tribe Name
Do not use this form for proposals to di	rill or to deepen or reentry to a different reservoir.	
Use "APPLICATION FO	R PERMIT—" for such proposals	
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
SOBMIT IN TRIFETORIE		
1. Type of Well		MCA Unit
Oil		8. Well Name and No.
2. Name of Operator		24
Conoco, Inc.		9. API Well No.
3. Address and Telephone No.		30-025-08061
10 Desta Dr. Ste 100W, Midland, TX 79705		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey D		Maljamar Grayburg/SA
	continues;	
660' FNL & 1980' FEL		11. County or Parish, State
Sec. 20, T-17S, R-32E		Lea
CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPOR	T OR OTHER DATA
- STESK ATTISTIBLE BOX	TO INDICATE NATURE OF NOTICE, REPORT	- CHOTIER BATA
TYPE OF SUBMISSION	TYPE OF ACTION	
₩		
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
•	Other Tost	Dispose Water
		(Note: Report results of multiple completion on Well
13 Describe Proposed or Completed Operations (Clearly state a	 Il pertinent details, and give pertinent dates, including estimated date of starting	Completion or Recompletion Report and Log form.) any proposed work. If well is directionally driller
	cal depths for all markers and zones pertinent to this work.)*	my proposed work. It went is directionally drained
It is proposed to perform the	following operations in order to prepa	re this well for
temporary abandonment:		
1. POOH with injection tubing	and packer.	
2. Set 4.5" cement retainer a	it 3625'.	
 Set 4.5" cement retainer a Pressure test @ 500 psi. 1 	for 30 minutes	
(Notify Carlsbad BLM off	ice and Hobbs OCD office 24 hrs. prior	क व्हुम ह
4. Circulaté packer fluid.		
		<u> </u>
		<>
		· · · · · · · · · · · · · · · · · · ·

		Si Ki
		<u> 2</u>
14. I hereby certify that the foregoing is true and correct		
14. I hereby teemy that the longging is the angeometr	Sr. Conservation Coordinat	or 11/11/94
Signed My Mittan	Title Sr. Conservation Coordinate	Date
(This space for Federa or State office use)	_	
Orig. Signed by Adam Salamah	Petroleum Engineer	Date 12/9/94
Approved by	Title	Date
••		
- SEE ATTACHED -		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements

CEIVED

1 4 1994

UCD HOBBS

OFFICE

BUREAU OF LAND MANAGEMENT CARLSBAD RESOURCE AREA

Temporary Abandonment of Wells on Federal Lands

Conditions of Approval

According to 43 CFR 3162.3-4-c, "No well may be temporarily abandoned for more than 30 days without the prior approval of the authorized officer".

Temporary Abandonment (TA) status approval requires a successful casing integrity test as follows:

- 1. Contact the appropriate BLM office at least 24 hours prior to the scheduled Casing Integrity Test. For wells in Eddy County call (505) 887-6544; for wells in Lea County call (505)393-3612.
- 2. A bridge plug or packer shall be set at a maximum of 50 feet above any open perforations or open hole.
- 3. All downhole production/injection equipment (tubing, rods, etc.) shall be removed from the casing if they are not isolated by a packer.
- 4. The production casing shall be filled with corrosion inhibited fluid and pressure tested to 500 psi. The casing shall be capable of holding this pressure for at least 30 minutes with a 10% allowable leak-off.

Wells that successfully pass the casing integrity test will be approved for Temporary Abandonment (TA) status for 12 months provided that the operator:

- 1. Submits a subsequent Sundry Notice requesting TA approval,
- 2. Attaches a clear copy or the original of the pressure test chart,
- 3. And attaches a detailed justification why the well should not be plugged and abandoned.

The TA status could be extended without another casing integrity test provided there was no leak-off during the test.

If the well does not pass the casing integrity test, then the operator shall within 30 days submit to BLM for approval one of the following:

- 1. A procedure to repair the casing so that a TA approval can be granted.
 - 2. A procedure to plug and abandon the well.