

REVISED

Form 2-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instructions
reverse side)ATE
in 10Form approved.
Budget Bureau No. 42-30424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029405 B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL & WL of Sec. 20, T-17S, R-32E,

Lea County, N. Mex.

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, RT, GR, etc.)

3977' DF

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit 14y 1

9. WELL NO.

63

10. FIELD AND POOL OR WILDCAT

Basil - Malvern - Russell

Lea County, N. Mex.

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA

Sec. 20, T-17S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) *Deepen in same formation*

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

In order to increase production, this well was deepened in the same formation and acidized by the following procedure:

Cleaned out & drilled to a new TD of 4027'. Stimulated 9th zone with 2,000 gals 20% LSTNE followed with produced water & chemicals. Ran mud anchor and perforated seating nipple on 2" tubing and set at 3924'. work completed 10-27-68.

Before work was done - tested 4980, 0 BW, 68 MCFG, 1593 GOR; After work completed - tested 11080, 56 BW, 37 MCFG, 335 GOR, 11-11-68

18. I hereby certify that the foregoing is true and correct

SIGNED

M. G. Yeakley

TITLE Administrative Section Chief

DATE

1-2-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

JAN 6 1969

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

V891-5 File