

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATA FE	
LE	
S.G.S.	
AND OFFICE	
PERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR RE-LEASE TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL OR TO REOPEN OR RE-LEASE TO A DIFFERENT RESERVOIR.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Mobil Producing TX. & N.M. Inc.

Address of Operator
9 Greenway Plaza, Suite 2700, Houston, Texas 77046

Location of Well
UNIT LETTER L 660 FEET FROM THE West LINE AND 3618 FEET FROM
THE North LINE, SECTION 2 TOWNSHIP 16-S RANGE 35-E MAPING.

15. Elevation (Show whether DF, RT, CR, etc.)

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

7. Unit Agreement Lease

6. Form of Lease Name
New Mexico "I"

9. Well No.
1

10. Field and Pool, or Wildcat
Townsend-Wolfcamp
See Summary Report
Supper Report 6-22-81

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPER. ☐ PLUG AND ABANDONMENT ☐

LL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOB ☐

OTHER ☐ OTHER Reperforate & acidize ☒

SUBSEQUENT REPORT OF:

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-16-81 MIRU Clark Well Service Ut. unseat pump. Hot oil rods w/35 B lease oil. POH w/rods & pump.

7-17-81 Inst BOP. POH w/10,394' tbgt. GIH w/pkr picker + 4-5/8 x 3-3/8 CR shoe, 2 - 3 1/2 DC's & 110 jts 2-7/8 N-80 tbgt work string.

7-18,19,-81 Fin GIH w/pkr picker to 10,200

7-20-81 Dry drl on Guib Model "A" pkr 10465-66 1/2, 18" 6 hrs.

7-21-81 Ran pkr picker back to bot, wash out fill 10465-66 1/2". Milled 10,466 1/2-67 - 6" 3 hrs. Pulled 290 jts 2-7/8" tbgt.

7-23-81 WIH w/4-5/8" OD x 3 1/4" ID Cut Rite Shoe, 2-3 1/2" Cols on 2-7/8" tbgt. to top of Guib Mode "A" pkr @ 10,465. Milled over pkr 1 1/2 hrs, pushed down 10' to 10475. Milled pkr loose 1 1/2 hrs. Pushed pkr down to PBTD @ 10585. Pulled shoe above perf.

7-24-81 POH w/shoe. WIH w/4-5/8" tooth Typr bit 5 1/2" csg. Scpr 2-3 1/2" cols on 2-7/8" tbgt. Tag pkr @ 10585. Pull 80 jts tbgt, FIN POH w/bit

7-27-81 Reperf 5 1/2" liner w/c zone, 1 JSPF 10269-10273, 10277-10281, 10322-10329, 10498-10520, 10527-10537 (99 holes) . Fluid level up to 200'. WIH w/Baker ret BP & "R" pkr on 2-7/8" tbgt to 4455 or 10' inside liner & stuck BP worked free, POH.

7-28-81 WIH w/5 1/2" Arrow Ret BP & Baker "A" pkr on 2-7/8" tbgt to 10,645 & stuck BP worked free, POH, 210 jts tbgt.

(Cont'd on back side)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

BY R.L. Hopper TITLE Authorized Agent DATE 9-1-81

APPROVED BY 1043 TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

17. (Cont'd)

- 7-29-81 POH w/pkr, did not rec BP WIH w/new pkr & BP ret head, latch on to BP @ 10465, pull free w/15 pts overpull, rest BP @ 10550, set pkr @ 10415.
- 7-30-81 Western Co. load csg w/110 bbls 2% KCL wtr, acidized Townson Wlfc perfs 10498-537 (68 holes) down 2-7/8 tbg w/5100 gal 15% NE, Fe HCL acid w/ 1/10% fric red, treating press 10 BPM, vac to 6600 psi, AIR 11 BPM @ 3500 psi, flushed w/60 bbl 2% KCL wtr @ 13 BPM BP @ 10550, could not set BP between perfs, POH, BP rubbers cut.
- 7-31-81 GIH w/RBP & pkr on 2-7/8 tbg & set RBP @ 10340 & test to 1000/OK. Set pkr @ 10166. Western Co. acidized Wolfcamp perfs 10269-10329 w/2700 gal 15% NEA Fe acid. Job complete @ 12:30 PM.
- 8-4-81 WIH w/30' MA, 4' x 2-3/8 perf tbg sub, SN, 14 jts 2-3/8 tbg 5-1/2 Guib TAC, 165 jts 2-3/8 8 RT tbg, 160 jts 2-7/8 tbg, set off BOP, set MA @ 10,550-80, perf sub @ 10,546-50, SN @ 10,545, TAC @ 10,113 w/12,000 T, press test tbg in hole 5000 psi, WIH w/2 x 1 1/4 x 20 Trico pump, 242 - 3/4 rods.
- 8-5-81 FIN GIH w/4-3/4", 102-7/8", 86-1" rods. Hung well on pump. 40 B hot wtr down tbg Press test 400/OK. Released Clark Well Service Ut & well to prod @ 1:30 PM.
- 8-26-81 NMOCD POT: P 34 BNO + 28 BLW/24 hrs, 6-1 1/4 x 144 SPM, GOR 2481/1, Grav 41.1 @ 60, Allow 34 (NP) TA 320', FINAL REPORT

NO. 10

8 193