

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| | | | | | |
|---|----------|--|----------|---|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | | NOTICE OF INTENTION TO PLUG BACK | | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | X | NOTICE OF INTENTION TO SHOOT (Nitro) | |
| NOTICE OF INTENTION TO GUN PERFORATE | X | NOTICE OF INTENTION (OTHER) | | NOTICE OF INTENTION (OTHER) | |

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

May 29, 1963

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Socony Mobil Oil Company, Inc.

New Mex "1"

Well No. 1 in L

NW SW (Company or Operator) 2

16 S

35 E

Townsend Wolfcamp

(Unit)

1/4 (40-acre Subdivision) 1/4 of Sec. T. 16 S, R. 35 E, NMPM, Pool

Lea County.

TD: 10,605'

PB: 10,585'

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Csg: 10 3/4" @ 462' w/340 sx., 7 5/8" @ 4630' w/2100 sx., 5 1/2" (Liner) 4445' to 10,605' w/1400 sx.

Perfs: 10,498-10,510'. Pkr. @ 10,465'.

Propose to pull rods, pump, tbq. and down hole separator. Rerun tbq. open ended w/seal assembly. Perf. 5 1/2" liner through tbq. 10,516-10,526' per ES survey or 10,527-10,537' per Western GR/N survey dated 11/12/55. Load hole w/oil. Brac w/10,000 gals Acid Kerosene emulsion (85% Acid + 15% Kerosene) in two stages. Drop 50 RCN ball sealers after 1st 5,000 gals. Pull tbq. Perf. 5 1/2" liner w/csg. gun 10,258-10,262; 10,266-10,270 & 10,311-10,318' per ES survey or 10,269-10,273; 10,277-10,281 & 10,332-10,329' per Western survey dated 11/12/55. All perfs. are one 1/2" Jet/ft. Run tbq. w/type AE plug under hookwall pkr. Set plug in pkr. @ 10,465'. Set hookwall pkr. @ 10,200' & treat perfs. w/10,000 gals Acid Kerosene emulsion (85% + 15%) in 3 stages. Drop 4 RCN ball sealers after 1st & 2nd stages. Unseat pkr. & retrieve plug. Rerun tbq. & separator and put back on production from all perfs.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Socony Mobil Oil Company, Inc.

By.....

Position.....

Group Supervisor

Send Communications regarding well to:

Name.....

Socony Mobil Oil Company, Inc.

Address.....

Box 2406, Hobbs, New Mexico