

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-08578
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Simmons Witt ASL
8. Well No.	1
9. Pool name or Wildcat	Townsend Morrow

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter <u>J</u> : <u>2310</u> Feet From The <u>South</u> Line and <u>2080</u> Feet From The <u>East</u> Line Section <u>11</u> Township <u>16S</u> Range <u>35E</u> NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3980' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-6-98 - Laid down drill collars. TIH with 2-7/8" tubing open ended to 586'. Displaced hole with 25#/bbl salt gel. Spotted a 100 sacks Class C cement plug with 2% CaCl₂ at 586'. TOOH. WOC 3 hours. TIH with tubing and tagged plug at 487'. Pulled up and set an 85 sack Class C cement plug with 2% CaCl₂ at 422'. TOOH. WOC 3 hours. TIH with tubing and tagged plug at 455'. Pulled up to 422'. Displaced hole. Spotted 135 sacks Class C with 2% CaCl₂ at 422'. TOOH. Shut well in for night.
5-7-98 - TIH with tubing and tagged plug at 294'. Pulled 1 joint to 261'. Spotted a 50 sack Class C cement plug with 2% CaCl₂ at 261'. Nippled down BOP. Ran 1 joint. Spotted a 30 sack Class C cement plug at surface. Cut off 13-3/8" casing. Cleaned location. Installed regulation abandonment marker with top of marker 2' below ground level and requested by Mr. Jerry Carlisle. Okayed by Jack Griffin w/OCD-Hobbs. PLUGGED AND ABANDONED - FINAL REPORT. Plugging completed 5-6-98.

NOTE: PLEASE SEE ATTACHED REQUEST ON DRY HOLE MARKER FROM JERRY CARLISLE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE May 18, 1998

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Chris Carlisle TITLE Chief Engineer DATE SEP 14 1998

CONDITIONS OF APPROVAL, IF ANY: