NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of	f Notice by Checking I	Selow	
NOTICE OF INTENTION COMMON PLANS	Notice of Intenti Temporarily Abas		Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well	Notice of Intents to Plub Back	ion	Notice of Intention to Set Liner	
Notice of Intention to Squeeze	Notice of Intenti to Acidize	ION	Notice of Intention to Shoot (Nitro)	
OTICE OF INTENTION O GUN PERFORATE	Notice of Intent:	NO	Notice of Intention (Other)	
DIL CONSERVATION COMMI CANTA PE, NEW MEXICO	SSION Hobbs, New	Mexico	September 26, 1	1960
Gentlemen:		(Fince)	(Date)	
Following is a Notice of Inter	ntion to do certain a pik as nose.	sibed below at the SOCC	ony Mobil Oil Company,	Inc.
	J. P. Caudi	11	Well No. 1 in	В
(Company 1/4 NE	or Operator)	R36E NMPA	Caudill Wolfcamp	(Unit)
TD: 11900'		N THE PULES AND	regulations)	
PBTD; 5850 Propose to spot 25 sl (4900' and Pull Csg. surface, with mud Lace cc: Humble 0il Compa	ks cement plug 5850° Spot 75 sks cement	to 5630'. Run plug 4900' to ugs. Install re	Free Point to 5000'. 4700', and spot 100 sl egulation marker.	Cut Cag ke at
PBTD; 5850 Propose to spot 25 sl (4900' and Pull Cag. surface, with mud Lac cc: Humble Oil Compa Sunray-Mid-Cont	ks cement plug 5850° Spot 75 sks cement den Fluid between plu any (SW/4 Sec. 9, T-) inent Oil Co. (SE/4 s	to 5630'. Run plug 4900' to ugs. Install re 15S, R-36E) Sec. 9, T-15S, Socony Mobil Position Distri	Free Point to 5000'. 4700', and spot 100 sl egulation marker.	K8 AC
PBTD; 5850 Propose to spot 25 sl (4900' and Pull Csg. surface, with mud Lace cc: Humble Oil Compa	ks cement plug 5850° Spot 75 sks cement den Fluid between plu any (SW/4 Sec. 9, T-) inent Oil Co. (SE/4 s	to 5630'. Run plug 4900' to ugs. Install re 15S, R-36E) Sec. 9, T-15S, Socony Mobil Position Distri Send	Free Point to 5000'. 4700', and spot 100 slegulation marker. R-36E) Oil Company, Inc. Company or Operator Company or Operator Ct Superintendent	to: