

NO.	COPIES RECEIVED
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-8944

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Skelly Oil Company	8. Name of Lease Name Mexico "E"
3. Address of Operator P. O. Box 1351, Midland, Texas 79701	9. Well No. 11
4. Location of Well UNIT LETTER B 801 FEET FROM THE North LINE AND 1839 FEET FROM THE East LINE, SECTION 2 TOWNSHIP 15S RANGE 37E N.M.P.M. Denton Wolfcamp	10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, SK, etc.) 3811' DF	12. County Lee

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Moved in casing pulling unit 8-28-73.
- Set 5-1/2" cast iron bridge plug at 9000' and capped with cement to 8975'.
- Shot off and recovered 5-1/2" OD casing at 4205'.
- Spotted 50 sack cement plug 4700-4800', 50 sack plug 4150-4255', 50 sack plug 2150-2275', and 10 sack plug from surface to 35'.
- Installed dry hole marker.

The 13-3/8" OD 48# casing, set at 322', and 8-5/8" OD 32# casing, set at 4771', were left in the hole. The unrecoverable portion of the 5-1/2" OD 17# casing from 4205-9181' was also left in the hole.

All intervals not cemented were filled with 10# mud.

Well plugged and abandoned 8-31-73.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED (Signature) D. R. Crow	TITLE Lead Clerk	DATE 9-10-73
APPROVED BY (Signature) John W. Remyan	TITLE (Signature)	DATE (Signature)
CONDITION OF APPROVAL, IF ANY:		