Form 9-331 (May 1963)

16.

UNIE STATES SUBMIT IN TRIPLICA' DEPARTMEN OF THE INTERIOR (Other instructions on verse side)

Form approved. Budget Bureau No. 42-R1424.

J. LEASE DES	10.14110.1	.1.10		•
10				
LC - 6	058	74	2	
			<u> </u>	
6. IF INDIAN,	ALLOTTE	E OR T	RIBE N	AME

GEOLOGICAL SURVEY									
CLINDRY	NOTICES	AND	REPORTS	ON	WELLS				

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME 1980' FSL & 660 FEL of SEC. 22

15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

Check Appropriate box to maleure traine of training of the control						
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:				
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (NOTE: Report results of multiple completion Completion Report and Log	CASING MENT* on on Well form.)		
(Other)	(0)	all partinout	details and give pertinent dates, including estimated of	late of starting		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Perf 41/2" esq w/2 JSPF from 3422' to 3425'. Treated perfs w/250 gals 15% acid. Squeezed perfs w/150 sks Class "C" cement. Drilled out & found csq collapsed @ 3421. Milled csq 3421-44' & squeezed w/50 sks cmt. Dritled out ¿ cleaned out to 3992'. Placed back on production.

SR. ANALYSZ SIGNED (This space for Federal or State office use) APPROVED BY GEOLOGICAL SURVEY CONDITIONS OF APPROVAL, IF ANY: *See Instructions on Reverse Sides. NEW MEXICO

HEAST MICH 3. File