


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

R. W. Fair

Box 516, Artesia, N. M.

Company or Operator

Address

Baish

Well No. 5

in NE 1-SE 1

of Sec. 22

T. 17S

R. 32E N. M. P. M. Maljamar Field, Lea County.

Well is 1980 feet N of the North line and 660 feet west of the East line of Sec. 22

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is M. E. Baish Address Artesia, N. M.

The Lessee is R. W. Fair Address " "

Drilling commenced 3/25/40 19 Drilling was completed 5/15/40 19

Name of drilling contractor C. C. Dodson Address Artesia, N. M.

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3855 to 3864 No. 4, from to

No. 2, from 3761 to 3768 No. 5, from to

No. 3, from 3859 to 3847 No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
1 1/2"				20'					
7"OD	20#	8		3540'	Plain				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	1 1/2"	20'	20			
8"	7"OD	3540'	400	Halliburton	Heavy	Circulated

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
	Tin	Nitre	200 qts	5/16	3840-3940	

Results of shooting or chemical treatment Flowed 700 bbls. on 24 hours test thru 7" casing.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3735 feet, and from feet to feet

Cable tools were used from 3735 feet to 4054 feet, and from feet to feet

PRODUCTION

Put to producing 5/16/40 19

The production of the first 24 hours was 700 barrels of fluid of which 100 % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Vernon Lane Driller O. E. Wood Driller

Driller L. M. Schooler Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 23rd

Artesia, N. M. May 23, 1940

Place

Date

day of May 19 40

Name Frank P. Collins

Position Book-keeper

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	23	23	Surface sand
23	160	137	Red rock
160	280	120	Red rock & gyp
280	665	385	Red rock
665	805	140	Red rock & gyp
805	830	25	Red rock
830	960	130	Anhydrite
960	2184	1224	Salt & Anhydrite
2184	2816	632	Anhydrite
2816	3104	288	Lime & Anhydrite
3104	3761	657	Lime
3761	3768	7	Lime (oil show)
3768	3775	7	Lime
3775	3781	6	Lime (gas)
3781	3839	58	Lime
3839	3847	8	Sandy lime
3847	3855	8	Lime
3855	3864	9	Sandy Lime (oil)
3864	3926	62	Lime
3926	3933	7	Sandy lime
3933	4037	104	Lime
4037	4045	8	Brown lime
4045	4054	9	Lime