

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SEE INSTRUCTIONS ON
REVERSE SIDE

6. LEASE DESIGNATION
LC 061434

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Ryder Scott Management Company		8. FARM OR LEASE NAME Mitchell	
3. ADDRESS OF OPERATOR 922 - 8th Street, Wichita Falls, Texas 76301		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FSL & 330' FWL		10. FIELD AND POOL, OR WILDCAT Maljamar Gbr SA	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 5 - 17 - 32	
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 4050' G. L.		12. COUNTY OR PARISH Lea	
		13. STATE N. M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) <input type="checkbox"/>	(Other) <input type="checkbox"/>

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-17-69: Set cast iron bridge plug at 3632' in 7" csg. with 3 sx cmt on top.
(7" csg. shoe at 3650') Filled hole with mud laden fluid.
Shot 8-5/8" csg. at 1620' & 1380'

Set 38 sx cmt. plug from 2850' to 2750' - in & out of csg. shoe
" 40 " " " 820' to 720' - in & out base of surface pipe.
" 10 " " " 24' to 0' - in & top of surface pipe.

Erected 4" metal marker; cleaned location.

Pulled 1398.11' of 8-5/8" casing.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

Agent

DATE 11-19-69

TITLE

APPROVED

MAY 12 1971

*See Instructions on Reverse Side

RECEIVED

MAY 18 1971

OIL CONSERVATION COMM.
HOBBS, N. M.