

COPY TO O. & C.

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
CONOCO INC.

3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 250' FNL & 250' FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

LC 029509 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

NICA

8. FARM OR LEASE NAME

NICA Unit

9. WELL NO.

29

10. FIELD OR WILDCAT NAME

Maljamar G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21, T-17 S, R-32 E

12. COUNTY OR PARISH

Lea

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
AUG 12 1980

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Due to poor csg. condition we plan to PLA subject well as follows:

Set cmt. retainer @ 3300'. Squeeze below retainer w/ 200 sx. class C cmt. & spot 5 sx. on top of retainer. Perf. @ 2950'-2951' w/ 2 JS PF.

Set retainer @ 2900'. Squeeze below retainer w/ 400 sx. class C cmt. & spot 5 sx. on top of retainer. Run sound log to determine if water flow is present below salt zone. Perf. @ 800'-801' w/ 2 JS PF. Set retainer @ 750'. Squeeze below w/ 400 sx. class C cmt. & spot 5 sx. on top of retainer. Check csg. valves @ surface for flow. Spot 10 sx. cmt. plug @ 50' to surface. Erect PLA marker & clear location. Verbal approval rec'd 8-6-80 per Jerry Long

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Butterfield TITLE Administrative Supervisor DATE 8/6/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

11545-5
MCA-K
FILE

APPROVED

AUG 20 1980

DISTRICT SUPERVISOR