

FOLD

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set
 Adapters—Material Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
3 1/2"		Nitro	90 gts	4-11	3875-3721	
4 "		"	50 "	4-13	3808-3828	3994

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 3992 feet, and from feet to feet

DATES

....., 19..... Put to producing , 19.....

The production for the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, °Bé.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Charles Pyatt, Driller C. W. Hammond, Driller
 Axel Walter, Driller, Driller

FORMATION RECORD

FROM	TO	TOTAL FEET	FORMATION
0	310	310	Red Bed
310	340	10	Thin shale
340	770	430	Red Rock + shale
770	885	115	Anhydrite
885	955	70	Red Bed
955	1735	780	Salt
1735	1755	20	Anhydrite
1755	1920	165	Salt
1920	3070	1150	Anhydrite
3070	3110	40	Red Sand
3110	3255	145	Anhydrite
3255	3260	5	Brown Lime
3260	3310	50	Anhydrite
3310	3330	20	Brown Lime
3330	3440	110	Anhydrite
3440	3697	257	Gray Lime
3697	3992	295	Lime

FORMATION RECORD—CONTINUED