oil

P. O. BOX 1980

Form Approved. Budget Bureau No. 42-R1424

UNITED STATESHOBBS, NEW MEXICO DEPARTMENT OF THE INTERIOR GEOLOGICAL SUBVEY

| J . | LEASE | |
|------------|-------|----------|
| | LC- | 02940560 |

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

| ACOLOGICAL SURVEY | | | | | | |
|-------------------|----------------|-----|----------------|----|------|---|
| | · | | | | | _ |
| SUNDRY | NOTICES | AND | REPORTS | ON | WELL | S |

| | _ | | | | | | _ | | _ | _ | _ |
|---|---|-----|----|----|----|----------|--------|----|---|---|-------|
| 7 | ī | 1 K | ur | 40 | DE | E | ٠, | īŦ | | | - |

| Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.) |
|--|
| |

Other injection well

MCA Unit 8. FARM OR LEASE NAME

well 2. NAME OF OPERATOR 9. WELL NO.

CONOCO INC.

3. ADDRESS OF OPERATOR

10. FIELD OR WILDCAT NAME

P. O. Box 460, Hobbs, N.M. 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

Valjamar (G/SA 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

AT SURFACE: 50 FNL \$2635 FWL AT TOP PROD. INTERVAL:

Sec. 30, T-175, R-32E 12. COUNTY OR PARISH 13. STATE

AT TOTAL DEPTH:

14. API NO.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

SUBSEQUENT REPORT OF:

Report results of multiple completion or zone ange on Form 9–330.)

REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON* (other) Convert to injection

OIL & GAS U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

1 5 1982

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 6/17/81. Drill out cont retainer at 3500'. CO to 3970'. Set pkn at 3500' Acidizew/ 1500 gals 15% HCL-NE-FE. Flush w/ 28 bbs. TFW. Placed on injection. 8/9/81: Inj. 418 BWPD at 1925 psi.

| Subsurface Safety Valve: Manu. and Type | Set @ Ft. |
|--|--------------|
| 18. I hereby certify that the foregoing is true and correct | |
| SIGNED WHILE Administrative | |
| ACCEPTED FOR RECORD is space for Federal of PETER W. CHESTER TITLE | |
| CONDITIONS OF APPROVA JUN 14 1982 | DATE |
| U.S. GEOLOGICAL SURVEY | |
| ROSWELL, NEW MEXICO - See Instructions on | Reverse Side |