

(May 1973)

DEPARTMENT OF THE INTERIOR

(Other instructions on reverse side)

Budget Bureau No. 42-R11.1

GEOLOGICAL SURVEY

5. LEASE DESIGNATION AND SERIAL NO.

LC 029410(b)

6. INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME MCA	
2. NAME OF OPERATOR Continental Oil Company		8. FARM OR LEASE NAME MCA Unit 1/4	
3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, New Mexico 88240		9. WELL NO. 106	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 50' FNL and 26.35' FNL of Sec 30		10. FIELD AND POOL, OR WILDCAT Mali G-SA Repress	
14. PERMIT NO.		15. ELEVATIONS (Show whether OF, RT, GR, etc.) 3930' df	
		12. COUNTY OR PARISH Lea	
		13. STATE N. Mex	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was deepened and Stimulated by the following procedures. WIH W/ 6 1/4" bit on 2 7/8" xbg and dird new hole from 3960'-3975'. Set pkr at 3950'. Tstd OH 3950'-3975' w/ 1000 gals 20% NE acid. Tstd 3881'-3916' w/ 3000 gals 15% HCL-NE acid. Tstd 3795'-3710' w/ 6,000 gals 15% HCL-NE acid. Frac'd OH 3575'-3718' w/ 20,000 gals gel wtr and 35,000 # 20/40 sand at 3800 psi at 19 BPM.

Test - before
Pmpd 10 BO and 14 BW in 24 hrs on 9-5-71.

Test - After
Pmpd 72 BO and 161 BW in 24 hrs on 10-6-71.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Supervisor

DATE

10-27-71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

OCT 28 1971

USGS (5) File

MCA(3)

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

RECEIVED

1971

U.S. DEPARTMENT OF AGRICULTURE
WASHINGTON, D.C.