

(SUBMIT IN TRIPLICATE)  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 029400-2  
Unit: **RECEIVED**  
SEP 5 - 1950  
OIL CONSERVATION COMMISSION  
HOBBS OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**Mitchell B**  
Well No. **IP #18** is located **2615** ft. from **N** line and **25** ft. from **E** line of sec. **20**  
**NE 1/4 Sec. 20** **17S** **32E** **RMPM**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Maljamar** **Lea** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

We submitted Notice of Intention to Drill this well on June 23, 1949, which application was approved, but the well was not drilled. We now propose to proceed with the drilling of this well are follows: Plats were filed with first notice

This well will be drilled with cable tools, and is to be used for a pressure maintenance gas injection well and is not to be used as an oil production well.

We will set approximately 60 feet of 10 3/4" OD casing for a conductor string, and cement it to the surface. We will then drill a 10-inch hole into the anhydrite at approximately 750 feet at which point the hole will be reduced to 8-inch and drilled to approximately 3850 feet which is just above the top of the 6th zone. We will set 7" OD seamless casing at this point and cement it with 250 sacks, preceded with sufficient mud to fill the hole to the surface. If 8 5/8" casing is run to shut off casing while drilling, it will be pulled prior to cementing the 7" casing. The well will then be drilled to an approximate depth of 4000 feet and will be tubed and equipped for gas injection.

Address 203 Carper Building  
Artesia, New Mexico

By [Signature]  
Title Vice-President

