

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
(Other instructions
reverse side)

Budget Bureau No. 1004-1
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL

LC-057210
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ OCT 13 11 03 AM '89

2. NAME OF OPERATOR Conoco Inc. CASE NO. AREAS

3. ADDRESS OF OPERATOR P.O. Box 460 - Hobbs NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface 2615'
2515' FSL + 2750' FEL

14. PERMIT NO. 30-02585012 15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7. UNIT AGREEMENT NAME MCA Unit Bly 3
8. FARM OR LEASE NAME

9. WELL NO. #182

10. FIELD AND POOL OR WILDCAT Maljamar G-SA

11. SEC. T, R., M., OR BLE. AND SURVEY OR AREA

27-T17S-R32E

12. COUNTY OR PARISH Lea 13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☒
(Other) Puddle Pack

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-16-89 Tag CIBP @ 3795'. Drill CIBP + jet wash 3862'-4070'.
Pump 40 Bbl 15% HCL-NE-FE acid. Pump 62 Bbl resin pack
3865'-4070'. DO 3884-87' and 3910-4070'. Dril junk 4070-
4082'. Dril new hole 4082'-4100'. Set liner @ 4100' w/175 sx
50/50 Perz "c" cmt. DO cmt to 4099'. Perf. 3885-3930,
3954-61', 3980'-85', 4042'-50', 4056'-60', 4065'-69'. Acidize
w/50 Bbl 15% HCL-NE-FE acid. Sand pack. CO. Place
well on prod.

Adm
CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED W.W. Baker TITLE Administrative Supv DATE Oct. 9, 1989
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side