

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION
P.O. BOX 1980
HOBBS NEW MEXICO 88240

Budget Code: No. 100-0155
Expires: March 31, 1993

5. Lease Designation and Serial No.
LC 029509A

6. If Indian, Altoner or Tribe Name

7. If Unit or CA, Agreement Designation

8920003410

8. Well Name and No.

MCA Unit # 41

9. API Well No.

30 025 12797

10. Field and Pool, or Exploratory Area

Maljamar Gray-SA

11. County or Parish, State

Lea County, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well:

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator:

Conoco, Inc. (005073)

3. Address and Telephone No.

686-5424

10 Desta Dr., Suite 100W, Midland, TX 779705 (915) 684-6381

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2530 FNL and 218' FEL
Sec 21, T-17S, R-32E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

P & A

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8-28-95: Move in, rig up, put on BOP, tally in hole with 2 3/8" workstring with RBP tool, latch onto bridge plug, pull out of hole, shut down.

8-29-95: Run 5 1/2" cement retainer, set at 3670', circulate mud, pump 40 sx under retainer 1000#, spot 15 sx on top from 3670-3530', 140' plug, perforate well at 895', pump 185 sx down 5 1/2" casing up 8 5/8" to surface.

8-30-95: Cut off wellhead, fill 10 3/4" surface casing with 20 sx cement, put in marker, rig down, move off.

Class "C" Cement

Mud - 25# salt gel per bbl

14. I hereby certify that the foregoing is true and correct

Signed

Title

Ann E. Ritchie
Regulatory Agent

Date

10-24-95

(This space for Federal or State office use)

Approved by

Title

Petroleum Engineer

Date

11/30/95

Conditions of approval, if any

RECEIVED
OCT 28 11 06 AM '95

