

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other Instructions on
reverse side)

Form approved.
Budget Bureau No. 42-B1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029509 (2)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

1650' FNL + 1650' FEL, SEC 21

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

BALSH A

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

BALSH-VERDES

11. SEC., T., E., N., OR BLK. AND SURVEY OR AREA

SEC 21, T-17S, R-32E

12. COUNTY OR PARISH 13. STATE

LEA

N. MEX.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

4045' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged & abandoned by the following procedures.

Set a 25 sx plug from TD to 2047'. Cut & pulled 4 1/2" seq. at 1009'. Spotted a 50sx plug in & out of 4 1/2" stub. Set a 25 sx cement plug in & out of surface casing. Placed a 10 sx plug at surface and capped with dry hole markers. 10 ft mud placed between each cement plug.

Locations have been cleared and are ready for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Adm. Supervisor

DATE 9-8-70

(This space for Federal or State office use)

APPROVED

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

SEP 31 1970

RECEIVED

APR 16 1970

OIL CONSERVATION COMM.
HOUSE, R. M.