Kemnitz

- Sinclair State Well Mo. 1
- Location: 660' frm the N/line 1980' frm the W/line, Sec. 27, 16S 34E.
- Elevation: 4092 Gr. 4104 D.F.
- 11/14/63: level location, preparing roads.
- 11/15/63: Finished location and roads.
- 11/16/63: Forester Drilling Co. moved in cable tool rig to set surface. Spudded 15" hole at 9:00 P.M. 11/16.
- 11/17/63: Drilling.
- 11/18/53: 110' surface sand, caliche and gravel.
- 11/19/63: 190' top of red bed at 180', drilling ahead.
- 11/20/63: 230' red bed.
- 11/21/63: 325', blue shale and red bed.
- 11/22/63: 357' red bed.
- 11/23/63: Moving in rotary and rigging up. 11/24/63: Set 10 3/4" csg at 403' w/400 sx Circulated--WOC
- 11/25/63: WOC
- 11/26/63: 2405' drlg shale and Anhydrite.
- 11/27/63: Drilling 3108' Anhyd. Mud 10.2, Vis. 33.
- 11/28/63: Drilling 3405' Anhy and gyp 1/2° at 3210'
- 11/29/63: Drilling 3572', Anhy and gyp 3/4° at 3485'.
- 11/30/63: Drilling at 3876' Anhy and gyp 1 1/4* 3745'.
- 12/1/63: Drilling at 4058' Anny 3/4° at 3953'.
- 12/2/63: Drilling 4280' Anhy and gyp 1/2° at 4135, mud wt. 10.4 Vis 32.