

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Plugged & Abandoned	5. LEASE DESIGNATION AND SERIAL NO. LC-029410-(b)
2. NAME OF OPERATOR CONTINENTAL oil company	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 460, Hobbs, NM, 88240	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FSL & 2310' FEL Sec. 30, T-17S, R-32E	8. FARM OR LEASE NAME CARPER-FEDERAL
	9. WELL NO. 1
	10. FIELD AND POOL, OR WILDCAT Wildcat
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30, T-17S, R-32E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3909' DF
	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐**RE-ENTER & REPAIR** ☒
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 12-23-76 Rig up P.U. Made Bit Trip to 4175'.
12-27-76 Ran Tbg w/pkr to 4120' and Pressured CSG Down Tbg - CSG ANNULUS TO 1500 PSI, Tested OK. Estimated Pump Rate 2 1/2 BPM AT 600 PSI. Pulled Packer.
12-28-76 Ran GR-Collar Log and Tagged OH Plug AT 5645', CSG Shoe AT 4185'. Ran Tbg with Retainer set AT 4030'. Pumped 75 SX Class C" CMT and Left 10' CMT ON TOP OF Retainer.
12-29-76 Loaded Hole with 11.6 PPG Mud. Spotted 25 SX Plug AT 1953'-1858'; Spotted 25 SX Plug AT 895'-800'; Spotted 25 SX Plug AT 474'-379'.
12-30-76 Spotted 10 SX CMT Surface Plug.
Erected Dry Hole Marker.
Released Rig 12-30-76

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAR 21 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

USGS (5), File

1 - 22 1977
CIL CONSERVATION COMA.
HOBBS, N. M.

1977-1978