



Shell Oil Company, #1 State "KS" - Sec. 27-158-37E

Wildcat

7-29-63

8-5-63

8-12-63

Drlg. 13700' ls. & ch.

Drlg. 14037' ls.

TD 14118', PB 14074', MO Rig.

DST 14007-047', open 4 hrs 35 mins, rec 34

bbls oil (gravity 51.6) + .5 B MC Salt Wtr, 60"

ISIP 5242#, FP 1213-1449#, 120" FSIP 5084#.

DST 14051-077', open 3 hrs, rec 5.1 B MC Sul.

Wtr + 51.7 B Sul. Wtr, 60" ISIP 3676#, FP 793-

1962#, 120" FSIP 2897#.

TD 14118', PB 14020', prep to perf.

Perf 6/14024-030', treated 500 gals acid, re-

treated 1000 gals acid. Swbd 122 BO + 158

BW in 12 hrs. Swbd 98% wtr in 3 hrs.

Set BP @ 14020' & squeezed perfs 14024-030'

with 25 sx.

8-26-63

TD 14118', PB 13082', swbg.

Perf 60/14001-016', treated 500 gals acid,

swbd 23 BNO + 12 BW in 12 hrs.

Squeezed Perfs 14001-016' with 45 sx.

Perf 20/12890-900', 36/12908-926', 8/12954-958',

12/12968-974', 20/12982-992', treated 300 gals

acid, swbd 61 BLO in 4 hrs.

9-3-63

TD 14118', PB 13082', prep to P&A.

Perfs 12890-992', swbd dry.

9-10-63

TD 14118', PB 13082', PLUGGED & ABANDONED.

LOG TOPS: Woodford 13880', Devonian 13992'.

Sample Tops: Des Moines 11700', Oolitic Lime

12350'.