

3D-025-20522

COUNTY <u>Lea</u>		FIELD <u>Maliamar</u>		STATE <u>N.M.</u>		NO. <u> </u>	
OPR. <u>Continental Oil Co.</u>							
NO. <u>234</u> LSE <u>MCA Unit-Federal</u>							
SEC. <u>21</u>		T. <u>17S</u>		BLK. <u>32E</u>		SUR. <u> </u>	
LOC. <u>25' fr S Line & 1325' fr W Line of Sec.</u>							
MI. <u> </u>		FROM <u> </u>		CLASS. <u> </u>		EL. <u> </u>	
SPUD. <u>6-10-63</u>		COMP. <u>7-26-63</u>		FORMATION <u> </u>		DATUM <u> </u>	
TRT. <u>F 60,000 gals +</u>		Log: <u> </u>		FORMATION <u> </u>		DATUM <u> </u>	
<u>60,000# sd</u>		Yates		2093'			
CSG. & SX. <u>8 5/8" 846' 780</u>		7 Rivers		2462'			
<u>5 1/2" 3721' 425</u>		Queen		3063'			
		San And		3828'			
TBG. DEPTH <u> </u>		SIZE <u> </u>					
LOGS EL GR RA IND HC A <u> </u>							
		TD <u>4100'</u>		dolo		PB	
PROD INT. <u> </u>		(DAILY RATE) <u> </u>		BS&W <u> </u>		GH <u> </u>	
<u>3721-4100'</u>		<u>Flo. 86 BO</u>		<u>14/64"</u>		<u>2022</u>	
<u>(San Andres) OH</u>				<u>36</u>		<u>580</u>	
				<u>400</u>		<u>24'</u>	

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. <u> </u>	PROP DEPTH <u>4100'</u>	TYPE <u> </u>
DATE <u> </u>		

F.R. 6-13-63, Gray burg
PD 4100'
6-17-63 Drlg. 3524'
6-24-63 TD 4100'; Reaming @ 3998'
Cored 3524-61', rec 37' dolo W/9' show
Cored 3561-3611', rec 50' dolo W/16' poor to fair show
Cored 3611-61', rec 50' dolo W/sli to good show
Cored 3661-3711', rec 50' dolo W/sli show
Cored 3711-48', rec 37' dolo W/16.5' scat sli show
Cored 3748-98', rec 50' dolo & sdy dolo W/fair to good show
Cored 3798-3848', rec 50' being:
10' anhy
40' dolo W/fair show

6-24-63 Continued
Cored 3848-98', rec 50' dolo W/26' scat shows
Cored 3898-3948', rec 50' dolo W/scat, sli show
Cored 3948-98', rec 50' being:
12.5' dolo W/sli show oil
37.5' dolo & shly dolo, NS
Cored 3998-4048', rec 50' dolo W/fair to good
show
Cored 4048-75', rec 27' dolo W/fair to good
show
Cored 4075-4100', rec 25' dolo W/sli to good
show
7-1-63 TD 4100' dolo; Swbg
Notched OH @ 3764', 3782', 3885', 4008', 4060',
Swbd 8 BLO in 6 hrs
7-8-63 TD 4100' dolo; Prep to frac

7-15-63 TD 4100' dolo; Flwg load
SOF 60,000 gals + 60,000# sd
Flo 339 BLO in 72 hrs thru 16/64" chk, TP 420#,
CP 640#
7-22-63 TD 4100' dolo; Flwg load
7-29-63 TD 4100' dolo; COMPLETED
8-1-63 COMPLETION REPORTED