

COUNTY LFA FIELD Kennitz, W. STATE NM
 OPR TIPTON, DWIGHT A. API 30-025-20593
 NO 1 LEASE State "31" MAP
Sec 31, T16S, R33E CO-ORD
660 FSL, 1980 FEL of Sec 4-3-32 NM
3 3/4 mi NE/Maljamar RESPD 3-1-83 RE CMP 3-7-83

CSC	WELL CLASS: INIT DX FIN DO LSE CODE			
	FORMATION	DATUM	FORMATION	DATUM
	ID <u>10,930 (PSLV)</u>	PBD	<u>10,500</u>	

IP (Wolfcamp) Perfs 10,404-430 P 18 BOPD + 27 BW.
 Pot based on 24 hr test. GOR TSTM; gty (NR)

CONTR OPRSELEV 4252 GL sub-s

F.R.C. 4-16-83 OWWO
 PD 10,500 WO
 (Orig. Aztec Oil & Gas Co., #3 Northeast
 Maljamar Unit, Temporarily Abandoned
 11-16-64, OTD 10,930, OPB 10,897)
 4-11-83 TD 10,930; PBD 10,500; Complete
 CIBP @ 10,500
 Perf (Wolfcamp) 10,404-430
 Acid (10,404-430) 6000 gals
 4-16-83 COMPLETION ISSUED

4-3-32 NM
 IC 30-025-70218-83

COUNTY	LEA	FIELD	Kemnitz, West	STATE	NM
OPR	AZTEC OIL & GAS COMPANY				MAP
3 Northeast Maljamar Unit					
Sec. 31, T-16-S, R-33-E					
660' fr S Line & 1980' fr E Line of Sec.					CO-ORD
Spud 8-21-64					
Temp. Abd. 11-16-64					CLASS
					EL 4252
CSG & SX TUBING	LOG:	FORMATION	DATUM	FORMATION	DATUM
13 3/8" 319' 315		Rust 1384			
8 5/8" 4412' 400		Queen 3605			
4 1/2" 10929' 250		SA 4380			
		Glor 5848			
		Clfk 6441			
		Tubb 7150			
		Hueco 9650			
LOGS EL GR RA IND HC A		TD 10930', PBD 10897'			

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. McVay Drlg. Co. PROP DEPTH 10750' TYPE

DATE

F.R. 8-13-64; Oper's Elev. 4241' G1
 PD 10,750' - Pennsylvanian
 8-25-64 Drlg. 1488'.
 9-1-64 Drlg. 4154'.
 9-9-64 Drlg. 5819'.
 DST 5015-5150', open 1 hr 30 mins,
 rec 370' drlg fluid + 180' sul wtr,
 30 min ISIP 1844#, FP 57-258#,
 1 hr FSIP 1603#.
 9-15-64 Drlg. 7466'.
 9-21-64 Drlg. 9112' lm.
 9-29-64 Drlg. 10492'.
 DST 10385-446', open 1 hr 10 mins,
 Rec 900' Gas in DP, 60' HO&SGCM + 270' SG&OCW
 1 hr ISIP 2130#, FP 65-109#,
 1 hr FSIP 1935#.

10-6-64 TD 10930', prep to run 4½" casing.
DST 10,785-895', open 2 hrs,
GTS 17 mins,
rec 400' oil, 760' HO&GCM + 210' salt wtr,
1 hr ISIP 2758#, FP 559-1738#,
1 hr FSIP 2337#.
DST 10836-930', open 2 hrs 35 mins,
GTS 7 mins,
Unloaded 1800' HO&GCM
rec 90' wtr below sub,
2 hr ISIP 2686#, FP 171-686#,
2 hr FSIP 2089#, HP 5085-5085#.

10-13-64 TD 10930'; PBD 10897'; Swbg.
Perf @ 10,862', 10,864', 10,866', 10,868',
10,870', 10,874', W/1 SPI.

10-20-64 Ac. 500 gals
Swbd 60 BLO + 8 BAW in 8 hrs.
TD 10930', PBD 10897', SI.
Perf 10844-856' W/4 SPF;
Re-Perf 10862-874' W/3 SPF
Ac. 5500 gals. 10844-874'
Swbd 41 BAW + 25 B salt wtr + 5 BNO in 9
hrs (10844-874')

10-27-64 TD 10930'; PBD 10897'; SI
11-2-64 TD 10930'; PBD 10897'; SI
11-9-64 TD 10930'; PBD 10897'; SI
11-16-64 TD 10930'; PBD 10897'; TEMPORARILY ABANDONED
SAMPLE TOPS: Rustler 1387', Glorieta 5848',
Clearfork 6424', Bursum Porosity 10432',
LOG TOPS: Bursum 10423', Kemnitz 10,696'.