

S 25 1980

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

## NEW MEXICO OIL CONSERVATION COMMISSION

P. C. D.  
ARTESIA, OFFICE

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
IND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
E - 10160

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- DRY WELL	7. Unit Agreement Name
2. Name of Operator MESA PETROLEUM CO	8. Farm or Lease Name KEMNITZ STATE
3. Address of Operator 1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701	9. Well No. 1
4. Location of Well UNIT LETTER M, 660' FEET FROM THE SOUTH LINE AND 660' FEET FROM THE WEST LINE, SECTION 22, TOWNSHIP 16S, RANGE 34E NMPM.	10. Field and Pool, or Wildcat HUME QUEEN
15. Elevation (Show whether DF, RT, GR, etc.) 4090' GR	12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Commenced P&A operations on 9-18-80. Set 5 sx "C" on CIBP at 4309'. Set Plug #1 with 20 sx "C" + 2% CaCl from 4100' to 4000'. Set Plug #2 with 20 sx "C" + 2% CaCl from 1660' to 1560'. Set Plug #3 with 20 sx "C" + 2% CaCl from 100' to surface and installed dry hole marker. Well plugged and abandoned 9-19-80.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

TO R. P. Nathan TITLE REGULATOR COORDINATOR DATE 9-24-80APPROVED BY Edd W. Long TITLE REGULATOR COORDINATOR DATE 9-24-80

CONDITIONS OF APPROVAL, IF ANY: XC: NMOC (6), TLS, CEN RCDS, ACCTG, HOBBS, MEC, JBH, PARTNERS, FILE