

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐ <u>etc. 1. action</u>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR <u>Chas. Cantel, Inc. (a.s.c.)</u>		8. FARM OR LEASE NAME <u>Harrison</u>	
3. ADDRESS OF OPERATOR <u>211 N. Main St., Dallas, Texas 75201</u>		9. WELL NO. <u>1</u>	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <u>1210' E. - 200' S.</u> <u>107' 100'</u>		10. FIELD AND POOL, OR WILDCAT <u>107' 100'</u>	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.)	
		12. COUNTY OR PARISH <u>LOG</u>	
		13. STATE <u>N. Mex.</u>	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Well drilled and completed 1210' true vertical 4360' (2012'). Was converted to water injection under gas ex in 1967. Injection discontinued in 1973. Well was plug 27-77, there were no other producing zones. The plugging procedure was witnessed by U.S.G.S. representative. Tubing was pulled into on top of packer at 4201'. In going back in hole with tubing bridge was set at 3371'. Could not work there. No. 1 plug of 25 sacks was placed thru tubing from 3360' to 3371'. Packer was engaged and 3 1/2" csg. circulated with 10% brine and mud. No. 2 plug thru tubing 25 sacks 2700'-2500'. No. 3 plug perforations (4 holes) made in 5 1/2" csg. at 1300'. Ran tubing, lined 75 sacks cement. 50 sacks passed out in perforations leaving 25 sack plug in 5 1/2" csg. 1300'-1100'. No. 4 plug 2 sacks 20' 0" in top of 5 1/2" csg. Steel cap welded on casing at 1100'. Casing pulled.

18. I hereby certify that the foregoing is true and correct

SIGNED Arthur R. Brown

TITLE Vice President

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

NOV 14 1977

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.