

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate*
(Other Instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1431.6. LEASE DESIGNATION AND SERIAL NO.
LC-029509(2)

7. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL OR WILDCAT

11. SEC., T., R., M., OR L.R. AND
SURVEY OR AREA

12. COUNTY OR PARISH

13. STATE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1780' FNL + 460' FWL of Sec. 22, T-175, R-32

in Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3999 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Work Done: Pulled tubing. Ran perforated seating nipple w/ Otis
type "N" landing nipple w/ no-go & Baker seal assembly,
w/ Otis type "S" landing nipple w/ side door coupling.
Ran 5 1/2" Baker blk-set packer w/ perforated seating
nipple & Otis type "S" landing nipple w/ perforated tripping
w/ fluid pack bottom hole assembly. Baker model "D"
packer set @ 9750', Otis type "N" landing nipple @ 9822'.
Otis type "S" landing nipple @ 9746'. Baker blk-set packer
@ 8902'. Otis type "S" landing nipple w/ bottom hole
assembly @ 8814'. Placed on production.

18. I hereby certify that the foregoing is true and correct

SIGNED

M. E. Yeakley

TITLE Administrative Section Chief

DATE

6-5-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

JUN 9 1969

USGS-5