NO. OF COPIES RECE	1 1		
	IVED		Form C-103 Supersedes Old
DISTRIBUTION	N		C-102 and C-103
SANTA FE		NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE		Aug 12 11 35 AM 265	5a. Indicate Type of Lease
U.S.G.S.			State X Fee
LAND OFFICE			5. State Oil & Gas Lease No.
OPERATOR			OG866
			
	SUNDRY NOT THIS FORM FOR PROPOSALS USE "APPLICATION FOR	TICES AND REPORTS ON WELLS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	7, Unit Agreement Name
1. 01L WELL	GAS OTH	HER-	N. E. Maljamar
2. Name of Operator			8, Farm or Lease Name
MONSANTO	COMPANY		
3. Address of Operato			9. Well No.
Drawer 16	329, Midland, Te	exas	1
4. Location of Well	- 1000		10. Field and Pool, or Wildcat West Kemnitz Lover Voltcamp
UNIT LETTER	1	FEET FROM THE FEET	
7 n - L		31 TOWNSHIP 168 RANGE 33E	NMPM.
THE KARL	LINE, SECTION	TOWNSHIP NAME	
THITTINITY		15. Elevation (Show whether DF, RT, GR, etc.)	12. County
			Les
PERFORM REMEDIAL W	77	PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS.	ALTERING CASING PLUG AND ABANDONMENT
Spudded 8-5-65:	At total depth surface w/300 shours.	of 400', set 377' - 10-3/4" 42# casing sx Class "A" cement w/2% cacl. Plug dom	at 395° and cemented to m 2:30 AM. WOC 21-1/2
other 17. Describe Propose work) SEE RULE	At total depth surface w/300 shours.	8-4-65. of 400'. set 377' - 10-3/4" 42# casing	at 395° and cemented to m 2:30 AM. WOC 21-1/2
OTHER 17. Describe Propose work) SEE RULE Spudded 8-5-65:	At total depth surface w/300 shours.	other S-4-65. of 400', set 377' - 10-3/4" 42# casing sx Class "A" cement w/2% caci. Plug does	at 395° and cemented to m 2:30 AM. WOC 21-1/2
OTHER 17. Describe Propose work) SEE RULE 8pudded 8-5-65:	At total depth surface w/300 shours.	other S-4-65. of 400', set 377' - 10-3/4" 42# casing sx Class "A" cement w/2% caci. Plug does	at 395° and cemented to m 2:30 AM. WOC 21-1/2
other	At total depth surface w/300 hours. WOC 2-1/2 hours	8-4-65. of 400', set 377' - 10-3/4" 42# casing sx Class "A" cement w/2% cacl. Plug does tested w/1000# for 30 min., held OK.	at 395° and cemented to m 2:30 AM. WOC 21-1/2
other	At total depth surface w/300 hours. WOC 2-1/2 hours	other S-4-65. of 400', set 377' - 10-3/4" 42# casing sx Class "A" cement w/2% caci. Plug does	at 395° and cemented to m 2:30 AM. WOC 21-1/2

CONDITIONS OF APPROVAL, IF ANY: