STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

40. 07 COPIES RECEIVES	
DISTRIBUTION	
SANTA FE	
FILE	
U.\$.G.\$,	
LAND OFFICE	
OPERATOR	

NO. OF COPIES RECEIVES	OIL CONSERVA	TION DIVISION	
DISTRIBUTION	Р. О. ВО.	X 2088	Form C-103 -
BANTA FE	SANTA FE, NEW	MEXICO 97501	Revised 10-1-78
FILE		MEXICO 87301	
U.\$.G.\$,			5a. Indicate Type of Lease
LAND OFFICE			State X Fee
OPERATOR			5, State Oll & Gas Lease No.
			E-10160
SLINDRY NO.	TICES AND REPORTS ON	WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS	TICES AND REPORTS ON	ACK TO A DIFFERENT RESERVOIR.	
USE APPEICATION FOR	2011 2 (7012 610,7701 300	n entrosace.;	7. Unit Agreement Name
OIL X GAB OTH	IER-		
, Name of Operator			8. Farm of Lease Name
Tipton & Denton		Kemnitz L/WC East Unit	
. Address of Operator			9. Well No.
c/o 0il Reports & Gas Serv	ices, Inc P.O. Box 7	63, Hobbs, NM 88241	2
. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER <u>K</u> , 1980	FEET FROM THE SOUTH	1980	Kempitz Lover Wolfeem
UNIT CETTER			THE PROPERTY OF THE PARTY OF TH
THE West LINE, SECTION)? 160	2 / F	
THE WEST LINE, SECTION	TOWNSHIP 105	RANGEN	MPM. (
	15. Elevation (Show whether	DF RT GR etc.)	12. County
	\sim	,,	(1)
<i>``````</i> ``````````````````````````````	4086 GR		Lea (\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Check Appropriate Check Check Appropriate Check	priate Box To Indicate N	ature of Notice, Report or	Other Data
NOTICE OF INTENT	TION TO:	SUBSEQU	IENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOS	The same and same at the same
PULC ON ACIEN CARING	CHARGE FEATS	OTHER Repair Casin	। no Leak তি
	٢ ا	STHER TOPALL CASL	ng Leak [X]
OTHER			
7. Describe Proposed or Completed Operation	(611		
/, Describe Proposed or Completed Operation:	s (Greatry state all pertinent deta	iiis, ana give pertinent aates, incli	uaing estimated date of starting any proposed

Work began 8/11/83. Found hole in casing between 6566 & 6630. Set retainer at 6316 & squeezed hole with 294 sacks @ 2100#. Drilled out retainer & cement to 6610. Pressure tested casing with 1,000#, test 0. K. Returned well to production. 9/20/83 pumped 35 bbls oil, 105 bbles water, 74 MCF gas 24 hours.

				•
hereby certify that the information above is true and compl	ete to the best	of my knowledge and belief.		
10 plane Doller	**************************************	Agent	DATE	9/23/83
				OCT 19 1983
OF APPRISTRICT J. SHOWN SEXTON	* T E		DATE	1 1 1383

教育の行う

23 1983

MOSES CHICE