

COUNTY	LEA	FIELD	Maljamar	STATE	NM
OPR	STANDARD OIL CO. OF TEXAS				MAP
	34. Iles-Federal Report 2				
	Sec. 15, T-17-S R-32-E				CO-ORE
	660' fr N & E Lines of Sec.				
	Spd 3-20-65		CLASS		
	Cmp 5-2-65		E		
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG			
		Anhy 980			
8 5/8" 1027' 400		Queen 3250			
4 1/2" 4358' 400		Gryb 3685			
		SA 4011			
LOGS EL GR RA IND HC A					
		TD 4358', PBE 4322'			

IP Grayburg Perfs 3829-3957' Pmpd 17 ROPD + 10 SW. Pat. Based on 24 hr test, gravity 36.1, GOR 10,200.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. McFarland PROP. DEPTH 4500' TYPE
DATE

P.R. 3-18-65
 PE 4500' - SA
 Contractor - McFarland
 3-22-65 TD 1027', prep to drill
 3-29-65 Coring @ 3728'
 4-3-65 Coring @ 4018'
 Cored 3696-3756', rec 60' anhy & dolo., w'NS.
 Cored 3756-3816', rec 60' anhy & dolo.
 Cored 3816-62', rec 46' anhy., dolo & sd.
 Cored 3862-3922', rec 60' anhy., dolo & sd.
 Cored 3922-3982', rec 60' anhy., dolo & sd.
 4-12-65 TD 4358', prep to run casing.
 Cored 3982-4042', rec 60' dolo & sd.
 Cored 4042-4102', rec 60' dolo.
 Cored 4102-62', rec 60' dolo.
 Cored 4162-75', rec 13' dolo.

4-20-65 TD 4358', prep to frac.
Perf @ 3829', 3831', 3833', 3835', 3837',
3895', 3897', 3899', 3901', 3937', 3939',
3941', 3943', 3945', 3954', 3957' W/1 SPI
Acc. 150 gals.
4-25-65 TD 4358', RU Pump
Frac 20,000 gals wtr + 21,000# sd. 3937-3957'.
Frac 10,000 gals wtr + 12,000# sd. 3895-3901'.
Frac 10,000 gals wtr + 12,000# sd. 3829-3837'.
5-3-65 TD 4358', pmpg load.
Pmpd 28 BNO + 57 BLW in 16 hrs.
5-10-65 TD 4358', PBD 4322', pmpg load.
Pmpd 8 BO + 10 BLW in 10 hrs.
5-17-65 TD 4358', PBD 4322', COMPLETED.