

COUNTY LEA FIELD Maljamar STATE NM

OPR STANDARD OIL CO. OF TEXAS MAP

36 Iles-Federal Report 2

Sec. 15, T-17-S, R-32-E CO-ORD

660' fr N Line & 1980' fr E Line of Sec.

Spd 5-25-65

Cmp 7-25-65

CSG & SX . TUBING	CLASS			
	FORMATION	DATUM	FORMATION	DATUM
	LOG:			
8 5/8" 309' 200	SA 3944			
4 1/2" 4200' 650	Low. Sd.			
	4118			

LOGS EL GR RA IND HC A

TD 4200', PBD 4150'

IP Grayburg-San Andres Perfs 3809-4135' Pmpd 20 BOPD + 3 BW.
Pot. Based on 24 hr test, gravity 37.6, GOR 2920.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 4500' TYPE

F.R. 5-20-65
PD 4500' - SA
6-1-65 Drlg. 3910'.
6-7-65 TD 4200', PBD 4155', WOC.
6-14-65 TD 4200', PBD 4155', prep to drill out cmt.
Perf @ 3955' & sqzd w/85 sx.
Perf @ 3940' & sqzd w/150 sx.
Perf @ 3830' & sqzd w/175 sx.
6-21-65 TD 4200', PBD 4150', WOC.
Drld out to 4150'
Perf @ 3809', 3811', 3813', 3841', 3843',
3845', 3847', 3851', 3853', 3875', 3877',
3879', 3903', 3905', 3949', 3951', 3987',
3989', 3991', 3993', 4133', 4135' W/1 SPI
Ac. 153 gals (4133-35')
Had communications.
Set BP @ 4092'
Sqzd perfs 3809-3993' W/200 sx.

6-28-65 TD 4200', PBD 4150', RU Pump.
DO to 4150'
Re-Perf @ 3809', 3811', 3813', 3841',
3843', 3845', 3847', 3851', 3853', 3875',
3877', 3879', 3903', 3905', 3949', 3951',
3987', 3989', 3991', 3993' W/1 SPI
Re-Ac. 700 gals.,
7-6-65 TD 4200', PBD 4150', tstg on pump.
Frac 50,000 gals wtr + 25,000# sd. 3809-4135'
Pmpd 5 BLW/24 hrs.
7-12-65 TD 4200', PBD 4150', swbg load.
Swbd 96 BLW/5 hrs (-484 BLW)
7-19-65 TD 4200', PBD 4150', pmpg load.
Pmpd 11 BLW/24 hrs. (-237 BLW)
7-26-65 TD 4200', PBD 4150', pmpg load.
8-2-65 TD 4200', PBD 4150', COMPLETED.