

COUNTY	LEA	FIELD Livingston-Paddock		STATE	NM
OPR	TIDEWATER OIL COMPANY			MAP	
10 State "P"					
Sec. 32, T-16-S, R-37-E				CO-ORD	
660' fr S Line & 1980' fr E Line of Sec.					
Spd 3-25-65		CLASS		EL [REDACTED]	
Cmp 5-22-65					
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
		Anhy 1995			
8 5/8" 2097' 1345		Yates 3095			
5 1/2" 6399' 1210		SA 4680			
		Glor 6051			
		Padd 6152			
LOGS EL GR RA IND HC A					
		TD 6400'			

IP Paddock Perfs 6133-6331½' Pmpd 50 BOPD + 7 EW. Pot. Eased on 24 hr test, gravity 34.3, GOR 520.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 6300'	TYPE
DATE		

F.R. 1-14-65; Oper's Elev. 3805' Df.
PD 6300' - Paddock
3-29-65 ID 2100', WOC.
4-5-65 Drlg. 4800'.
4-12-65 Drlg. 5070'.
4-19-65 Drlg. 6105'.
4-26-65 ID 6400', WOC.
Cored 6175-6235', rec 59½' dolo., frac, w/show oil & gas.
Cored 6235-94', rec 59' dolo., w/scatt frags, trace to fair show of oil & gas.
Cored 6294-6353', rec 59' dolo., w/sh partings, & frags, fair to medium show of oil & gas.
Cored 6353-6400', rec 47' dolo., w/scatt bldg oil, gas & wtr.

5-3-65

TD 6400', RJ Pump.
Perf @ 6133', 6145', 6157', 6170½', 6181',
6194', 6217', 6230', 6259', 6281½', 6331½'
w/1 SF1
Ac. 1000 gals.
Prod 10,000 gals jel acid + 10,000# sd.
In-Ac. 3000 gals. 6133-6331½'
Rate 116-110 in 7 hrs.

5-10-65

TD 6400', pmprg load.

5-17-65

TD 6400', pmprg load.

5-24-65

TD 6400', COMPLETED.