

INSTRUCTIONS

This form is to be filled with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filled in quintuplicate except on state land, where six copies are required. See Rule 1155.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	1490	T. Canyon	Ojo Alamo
T. Salt	1600	T. Strawn	Kirtland-Fruitland
B. Salt	2505	T. Atoka	T. Pictured Cliffs
T. Yates	2616	T. Miss	T. Cliff House
T. 7 Rivers	3445	T. Devonian	T. Menefee
T. Queen	3445	T. Silurian	T. Point Lookout
T. Grayburg	4245	T. Montoya	T. Mancos
T. San Andres	5283	T. Simpson	T. Gallup
T. Glorieta		T. McKee	Base Greenhorn
T. Paddock		T. Ellenburger	T. Dakota
T. Blinberry	7035	T. Gr. Wash	T. Morrison
T. Tubb		T. Granite	T. Todilto
T. Drinkard	7703	T. Delaware Sand	T. Entrada
T. Abo	9180	T. Bone Springs	T. Wingate
T. Wolfcamp		T. Permian	T. Chinle
T. Cisco (Bough C)	10235	T.	T. Penn. "A"

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	220	220	Sand & caliche				
1490	1600	110	Anhydrite				
1600	2505	905	Salt				
2505	2616	111	Anhydrite				
2616	2880	264	Sand & anhydrite				
2880	3445	565	Anhydrite				
3445	3900	455	Sand & anhydrite				
3900	4245	345	Anhydrite				
4245	5283	1038	Dolomite				
5283	5820	537	Sand & dolomite				
5820	7035	1215	Dolomite				
7035	7230	195	Sand & dolomite				
7230	7703	473	Dolomite				
7703	8380	677	Shale & dolomite				
8380	9180	800	Dolomite				
9180	10235	1055	Lime & shale				
10235	10285	50	Dolomite				

DRILL STEM TEST: 10,084-10,118' Tool open 60 minutes. Recovered 380' mud and sulphur water, and 4620' sulphur water.