

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

HUBBARD OIL CO. D.C.C.
JUN 7 1 09 PM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. -
7. Unit Agreement Name -
8. Farm or Lease Name J. E. Stokes, et al
9. Well No. 1
10. Field and Pool, or Wildcat Shoe Bar - Penn.
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER -
2. Name of Operator Ashman & Hilliard
3. Address of Operator 710 Vaughn Building, Midland, Texas 79701
4. Location of Well UNIT LETTER "G" 1980 FEET FROM THE North LINE AND 2310 FEET FROM THE East LINE, SECTION 26 TOWNSHIP 16-8 RANGE 35-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3964 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Operator drilled well to TD 10,485' on 3/31/66, ran & cemented 5 1/2" casing as follows:

105 jts 17# new N-80
151 jts 17# new J-55
71 jts 17# buttress

5 1/2" casing set at 10,478'. Cemented w/200 sx 50/50 Posmix Incore, 100 sx regular Neat. WOC 24 hrs. Top of cement by temperature survey 8850'. Pressured up to 1000# for 30 minutes. Held okay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jim E. West TITLE Production Supt. DATE April 9, 1966

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: