

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
J. M. Huber Corporation
3. ADDRESS OF OPERATOR  
1900 Wilco Building
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FEL & 2130' FSL  
AT TOP PROD. INTERVAL: 1980' FEL & 2130' FSL  
AT TOTAL DEPTH: 1980' FEL & 2130' FSL
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

## SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☒  
☐  
☐  
☐  
☐

5. LEA  
NM015072
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Stoltz Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Morton Wolfcamp
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 12, R-15S-T-34E
12. COUNTY OR PARISH  
Lea
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4057' GR.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 1) Set RBP @ 6639' and spotted 40' sand on top of RBP.
- 2) Set RTTS pkr. @ 5639'. Pumped 500 gals. 15% HCL acid and established injection rate 5 BPM @ 2000#. POH w/RTTS pkr.
- 3) Set E-Z Drill cmt. retainer @ 5639' on wireline.
- 4) Stung into cmt. retainer w/tbg. & cmt. w/240 sks. Class "C" cmt. Squeezed csg. leak to 2700psi.
- 5) SWI 48 hrs. Drilled out cmt. retainer & cmt. and tested casing to 750#. Retrieved BP and put well on production.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert G. Setzler TITLE Dist. Prod. Mgr DATE August 29, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

