

NEW MEXICO OIL CONSERVATION COMMISSION

OF COPIES RECEIVED		
DISTRIBUTION		
SA A FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
NM 015072

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL  GAS WELL  OTHER

2. Name of Operator  
J. M. HUBER CORPORATION

3. Address of Operator  
1900 Wilco Building, Midland, Texas 79701

4. Location of Well  
UNIT LETTER J 1980 FEET FROM THE East LINE AND 2130 FEET FROM  
THE South LINE, SECTION 12 TOWNSHIP 15S RANGE 34E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name  
Stoltz Federal

9. Well No.  
1

10. Field and Pool, or Wildcat  
Morton Wolfcamp

15. Elevation (Show whether DF, RT, GR, etc.)  
4057' GR.

12. County  
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>Repair Casing Leak</u> <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JQB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- To repair casing leak by squeezing with cement and;
- 1) Set CIBP @ 9790' in 4½" casing @ approx. top of original cement.
  - 2) Shoot 4-way jet 9720'.
  - 3) Run tbg. & pkr. & break circulation to surface.
  - 4) Cement w/sufficient volume to cover 4½" pipe from 9720' to 5650'.
  - 5) Set cement retainer @ 4300'.
  - 6) Cement w/sufficient volume to tie cement back into the intermediate csg.
  - 7) Drill out & pressure test re-squeeze if necessary.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert C. Betzler

TITLE District Production Mgr. September 7, 1978

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

