

COUNTY	IFA	FIELD	Wildeat	STATE	NM
OPR	McBEE OIL COMPANY				
	1 Moreman				
	Sec. 3, T-15-S, R-38-E				
	660' FSL, 660' FEL of Sec.				
	Spd 12-1-65				
	Cmp 3-2-66				
	CLASS		E		
CSG & SX - TUBING	FORMATION	DATUM	FORMATION	DATUM	
13 3/8" 363' 350					
8 5/8" 4900' 400					
4 1/2" 6370' 450					
LOGS EL GR RA IND HC A					
	TD 13023'				
PLUGGED & ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Wharton Drlg. Co. PROP DEPTH 13,200' TYPE
DATE

F.R. 11-24-65
PD 13,200' - Devonian
Contractor - Wharton
12-6-65 Drlg. 4358'.
12-13-65 Drlg. 5963'.
12-20-65 Drlg. 7960' lm.
1-3-66 TD 10526', fshg DP.
1-10-66 TD 10526', fshg.
1-17-66 Drlg. 11100' lm & ch.
1-24-66 Drlg. 11947' lm & sh.
1-31-66 Drlg. 12552' lm & ch.
2-7-66 Drlg. 12995'.
DST 12850-985', open 1 hr,
Rec 90' gas in DP, 20' free oil (Gravity
45.) + 250' HO&GCM,
1 hr ISIP 4565#, FP 1399-1412#,
1 hr 7 min FSIP 4284#.

14-66 TD 13023', running casing on San Andres.
DST 12850-13,000', mis-run.
DST 12850-13,000', open 1 hr,
Used 2880' WB,
Rec 2535' Sli O&GWB, 390' Sli O,G &
MCWB + 90' HO&GCM,
2 hr ISIP 4866#, FP 1425-1441#,
2 hr FSIP 4802#.
DST 12850-13023', open 1 hr,
Rec 2068' WB, 560' O,G & Salt Wtr CM,
+ 2394' Salt Wtr,
1 hr ISIP 4892#, FP 1296-2302#,
1 hr FSIP 4854#.
2-21-66 TD 13023', PBD 6370', prep to perf.

2-28-66 TD 13023', PBD 6370', prep to P&A.
PB to 6370'
Perf @ 5943', 6117', 6125', 6135',
6181', 6224', 6228' W/2 SPI
Ac (5943-6228') 500 gals.
Swbd load & swbd 18 BWPH, w/NS.
Perf @ 5543', 5582', 5588', 5595'
W/2 SPI
Ac (5543-95') 500 gals.
Swbd dry
Perf @ 5344', 5356', 5436', 5448',
5452' W/2 SPI
Ac (5344-5452') 500 gals.
Swbd dry

LEA Wildcat NM
McBEE OIL CO., #1 Moreman

Sec. 3-15S-38E

Page #3

3-7-66 TD 13023', PBD 6370', PLUGGED & ABANDONE D.
LOG TOPS: Yates 3241', Glorieta 6377',
Tubb 7508', Abo 8205', Woodford 12863',
Devonian 12972'.

1-256