

COUNTY	LEA	FIELD	Lovington	STATE	NM
OPR	TENNECC OIL COMPANY			MAP	
	3 State "Q"				
	Sec. 30, T-16-S, R-37-E			CO-ORD	
	2310' FNL, 330' FWL of Sec.			MN 21792	
	Spd 6-4-66			CLASS	
	Cmp 10-21-66			E	
	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING					
8 5/8" 2105' 640					
4 1/2" 6450' 595					
LOGS EL GR RA IND HC A					
	TD 6450'				
TEMPORARILY ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	6500'	TYPE
DATE			

F.R. 6-9-66
PD 6500' - Paddock

6-13-66 Drlg. 3817'.

6-20-66 Drlg. 5337' 1m.

6-27-66 TD 6450', WOC.

7-5-66 TD 6450', SI.

7-11-66 TD 6450', PBD 6382', WO Pumping Equip.
Perf @ 6119', 6131', 6137', 6196', 6230',
6242', 6296', 6307', 6321', 6326' W/1 SPI
Acid (6119-6326') 1000 gals.
Frac (6119-6326') 20,000 gals jelled acid
+ 20,000# sd.

7-18-66 TD 6450', PBD 6382', WO Pumping Equipment.

7-25-66 TD 6450', PBD 6382', TO Pump.

8-1-66 TD 6450', PBD 6382', TO Pump.

8-8-66 TD 6450', PBD 6382', TO Pump.

8-15-66 TD 6450', PBD 6382', TO Pump.

8-22-66 TD 6450', PBD 6382', TO Pump.

8-29-66 TD 6450', PBD 6382', TO Pump.

9-6-66 TD 6450', PBD 6382', TO Pump
Ppd 5 BO + 40 BW/24 hrs (6119-6326')
9-12-66 TD 6450', PBD 6382', TO Pump.
Ran Tracer Survey;
9-19-66 TD 6450', PBD 6382', Drlg Cmt.
Squeezed perfs 6119-6326' W/200 sx.
10-3-66 TD 6450', PBD 6382', SI.
10-10-66 TD 6450', PBD 6382', pmpg load.
Perf @ 6119', 6131', 6137', 6196',
6230', 6242', 6296', 6307', 6321',
6326' W/1 SPI
Acid (6119-6326') 1000 gals.
Frac (6119-6326') 20,000 gals jelled acid
+ 20,000# sd.
Pmpd 20 BLW/24 hrs (6119-6326')
10-17-66 TD 6450', PBD 6382', pmpg load.

10-24-66 TD 6450', PBD 6382', tstg.
11-7-66 TD 6450', PBD 6382', tstg.
11-14-66 TD 6450', PBD 6382', TEMPORARILY ABANDONED.
Pmpd 18 BFW Per Day (6119-6326')
LOG TOPS: Anhydrite 2118', Top Salt 2234',
Base Salt 2988', Yates 3090', Seven Rivers
3384', Queen 3975', San Andres 4703',
Glorieta 6095'.