

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

JAN 24 3 02 PM '67

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. -
7. Unit Agreement Name -
8. Farm or Lease Name Daisy Clayton
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Ashmun & Hilliard
3. Address of Operator 710 Vaughn Bldg., Midland, Texas 79701
4. Location of Well UNIT LETTER M , 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 15-S RANGE 33-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4179' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Operator proposes to plug and abandon as soon as approval to do so is received from the Commission.

Will shoot off and pull 5 1/2" csg. Plugs to be set as follows:

- 50' 10 sx plug in perforations 9588'-98'
- 50' 25 sx plug in stub of 5 1/2" csg @ approx. 9000' (anticipate shooting off here)
- 50' 25 sx plug @ 7800' Abo
- 50' 25 sx plug @ 7000' Drinkard
- 50' 25 sx plug @ 5840' Glorieta
- 50' 25 sx plug @ base of 8 5/8" csg. @ 4189'
- 50' 25 sx plug in stub of 8 5/8" csg. @ approx. 1600'
- 50' 25 sx plug in base of 11 3/4" csg. @ 333'
- 30' 10 sx plug in top of 11 3/4" csg.

Mud will be applied between all plugs from TD back to surface.
Surface marker will be set in top of cement.
Location to be cleared.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Superintendent DATE Jan. 25, 1967

APPROVED BY [Signature] TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: