

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

Cima Capitan Inc.

3. ADDRESS OF OPERATOR

211 N. Ervay, Rm. 1320 Dallas, TX 75201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FN & 990' FW Line

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other)

SUBSEQUENT REPORT OF

RECEIVED

APR 27 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE

LC 063867

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

HARRISON

9. WELL NO.

10. FIELD OR WILDCAT NAME

MALJAMAR

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3, T17S, R32E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4294 Gr.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well drilled and completed thru perforations 4345'-4144' in 1966.
85/8" csg. 379' cemented w/200 sacks, 5 1/2" csg. 4397' cemented w/300 sacks.
Plug #1 4110'-4125' C.I. Bridge plug to be set and 5 sack cement plug placed on top w/bailer.
Well will be circulated w/10# brine & mud
Plug #2 2300'-2500' 25 sacks cement plug to be spotted thru tubing
Plug #3 1100'-1300' Perf. csg. 1300', 75 sacks cement mixed and pumped thru tubing, 50 sacks squeezed thru perf., 25 sacks left in csg.
Plug #4 18'-40' 10 1/2 sacks cement placed in csg. Csg. to be cut 4' below surface level, steel cap welded on and marker placed.
Plug #5 330'-430' CEMENT PLUG INSIDE AND OUTSIDE 5 1/2" CSG ACROSS 8 5/8" CSG SHOE.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

C. W. Enagua

TITLE Agent

DATE April 24, 1981

APPROVED

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

Rogers A. Chapman

TITLE

DATE

MAY 22 1981

*SUBJECT TO THE ATTACHED CONDITIONS.

for JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

OIL CONSERVATION DIV.

JUN 2 81

RECEIVED