

UNITED STATES  
DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPLICATE  
(Other instructions on  
reverse side)

GEOLOGICAL SURVEY

HOBBS OFFICE O.C.C.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug a well to different user.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

Form approved.  
Budget Bureau No. 42-R-11-14.

5. LEASE DESIGNATION AND SERIAL NO.

LC 063867

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Harrison

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Maljamar

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 3, T17S, R32E

12. COUNTY OR PARISH 13. STATE

Lea

N. M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Cima Capitan, Inc.

3. ADDRESS OF OPERATOR

Box 1343, Artesia, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

990' FN & 990' FW

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4294 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐ surface casing job

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded at 12:00 Noon, 30 November 1966. Drilled 11" hole to 384'. Ran 9 joints - 8 5/8" 20# casing 365.66" with guide shoe 1.00'. Total string 366.66'. Landed at 379.36' (K B 10.70' above ground level.) K B is permanent datum. Cemented w/200sx regular w/2% CaCl. Full returns of cement to surface. Plug down 4:53 P.M. WOC 12 hours. Tested casing to 1000 psi. Held O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

\*See Instructions on Reverse Side

DEC 2 1966

J. L. GORDON  
ACTING DISTRICT ENGINEER