

COMPANY: Mobil Oil Corporation
ADDRESS: P. O. Box 633, Midland, Texas 79701 11 31 AM '67
LEASE: Marie Etcheverry Well #1
COUNTY: Lea, New Mexico

SUMMARY OF OPERATIONS

- 6/17 ¹⁻¹⁸³
~~1-183~~
1-183 (1) 375 ND red bed, 17½" hole, ½ @ 375. Spud mud.
Running 13-3/8 csg. A. W. Thompson, Inc. spudded in @ 5:00 p.m.
6/16/67.
- 6/19 ¹⁻¹⁶³
~~1-163~~
1-163 (3) 1996 drlg red bed, salt & anhy, 12¼" hole, 1/8 @ 1667. Br wtr.
Ran 375' 13-3/8" H-40 48# ST&C csg, cemented on bottom @ 375' by Howco
w/ 375x Incor Neat cement w/ 2½ HA5, PD @ 7:45 a.m. 6/17/67, cement circ,
WOC 20 hrs, tested BOP's & csg w/ 1000#/30 min/ok.
- 6/20 (4) 2631 drlg salt & anhy, 12¼" hole, 1° @ 2500. Br wtr.
- 6/21 (5) 3053 drlg anhy & salt, 12¼" hole, 1½ @ 2641. Br wtr.
Add 24 bbls diesel oil to brine wtr.
- 6/22 (6) 3383 drlg anhy, 12¼" hole, 3/4 @ 3324. Br wtr & diesel oil.
- 6/23 (7) 3773 drlg anhy, 12¼" hole, 3/4 @ 3595. Br wtr & diesel oil.
- 6/24 (8) 4038 drlg anhy, 12¼" hole, 3/4 @ 3927. Br wtr & diesel oil.
- 6/26 (10) 4454 drlg lm, 12¼" hole, 1° @ 4348. Br wtr & diesel oil.
- 6/27 (11) 4500 ND lm, 12¼" hole, 1½ @ 4500. 10.6-42-24.0.
Circ 3 hrs, pulled bit, Schl ran GR-S-Caliper & SP logs to 4499 in 7
hrs, ran bit to bottom, circ 2 hrs, now LD DP, prep to run 9-5/8 csg.
Elev DF 4144, Gr 4131, Top Rustler anhy 1750, Top Yates 2918, Top
Queen 3920, Top San Andres 4468, Schl TD 4499.
- 6/28 ¹⁻¹⁵⁷
~~1-157~~
1-157 (12) 4500 ND, WOC 9-5/8" csg, finish LD DP & DC's, ran 4500' of 9-5/8
csg - 428' of 40# J-55 ST&C + 4072 of 36.0# J-55 ST&C cemented bottom
@ 4500 by Howco w/ 1375x Incor 6½ gel salt saturated cement + 1/8 floccle
per sx in 1st 500x + 200x Incor Neat, PD 5:30 p.m. 6/27/67, cement circ,
nipple up 9-5/8 csg, inst'l BOP's, now prep to drill 8-3/4 hole.
- 6/29 ¹⁻¹⁵⁷
~~1-157~~
1-157 (13) 4580 drlg lm, 8-3/4" hole, NWD. Fresh wtr & soap.
Tested BOP's w/ 2000#/30 min/ok. WOC total 30 hrs.
- 6/30 (14) 4827 drlg lm, 8-3/4" hole, 3/4 @ 4636. Fresh wtr & soap.