

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	7. Unit Agreement Name
2. Name of Operator Union Oil Company of California	8. Farm or Lease Name Inas Tatum
3. Address of Operator P. O. Box 671 - Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER J , 1980 FEET FROM THE East LINE AND 1980 FEET FROM THE South LINE, SECTION 25 TOWNSHIP 15-S RANGE 34-E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4037.5' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:



PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PILL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 11,709' and received verbal permission to plug and abandon from John Runyan 10-17-67.
The proposed plugging program is as follows:

- 25 sack cement plug at total depth.
- 25 sack cement plug at top of Cisco.
- 25 sack cement plug at top of Abo.
- 25 sack cement plug at top of Glorieta.
- 25 sack cement plug at base and top of salt.
- 50 sack cement plug across shoe and cut on 8-5/8" casing.
- 50 sack cement plug across shoe of 11-3/4" casing.
- 10 sack cement plug at surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 	R. G. Ladd, Jr.	District Drilling Superintendent	October 19, 1967
APPROVED BY 			
CONDITIONS OF APPROVAL, IF ANY:		TITLE	DATE