	-			
. COPIES RECEIVED		Form C-103		
- TRIBUTION		Supersedes Old		
······		C-102 and C-103		
	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65		
U.S.G.S.		5a. Indicate Type of Lease		
┝ ╺╸╸ · · · · · · · · · · · · · · · · · ·				
OPERATOR		State XX Fee		
OPERATOR				
		K-4676		
LOO NOT USE THIS FORM FOR PRO	Y NOTICES AND REPORTS ON WELLS probals to drill or to deepen or plug back to a different reservoir. 104 for permit			
1.		7. Unit Agreement Name		
OIL GAS WELL	OTHER-			
2. Name of Operator		8. Farm or Lease liame		
Gulf Oil Corporation	1	Lea "PS" State		
3. Address of Operator		9. Well No.		
Box 670, Hobbs, N.M.	88240	2		
4. Location of Well		10. Field and Pool, or Wildcat		
UNIT LETTER,	1875 FEET FROM THE SOUTH LINE AND 2085 FEET FROM	No. Vac. Lower Wolf.		
THE West LINE, SECTION	DN 34 TOWNSHIP 165 RANGE 34E NMPM.	$\boldsymbol{\lambda}$		
		$\boldsymbol{\Sigma}$		
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County		
	4078' GL	Lea		
16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data				
		REPORT OF:		
	SUBSEQUENT	REFORT OF:		
PERFORM REMEDIAL WORK	PLUG AND ABANDON	ALTERING CASING		
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANCONMENT		
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB			
¢.	OTHER Plug and abandon			
OTHER				
17. Describe Proposed or Completed Op work) SEE RULE 1103.	erations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed		

10,835' TD.

1-

Pulled producing equipment. Ran Baker Model N CIBP on 2-7/8" tubing and set BP at 10,600[•]. Circulated hole with plugging mud and capped BP with 4 sacks cement. Cut and recovered 5-1/2" casing from 6990[•]. Spotted 20 sack cement plug from 7040-6940[•]. Spotted 29 sack cement plug 6150-6050[•]. Spotted 29 sx cmt plug 4670-4570[•]. Spotted 30 sack cement plug 4139-4039[•]. Cut and recovered 8-5/8" casing from '898[•]. Spotted 50 sack cement plug from 948-848[•] across 8-5/8" casing stub. Spotted 72 sack cement plug from 456-356[•] across 13-3/8" casing shoe. Pushed Howco wooden plug to 13[•]. Spotted 10 sack surface plug. Installed dry hole marker. Plugged and abandoned 4-16-74.

Will advise when location is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED	Sandiaz	TITLE Area Engineer	DATE 4-16-74	
	Col- Signed by			
APPROVED BY _	í	TITLE	DATE	
CONDITIONS OF APPROVAL, IF ANY:				

NU ED

V. ... 1. - M.C. OIL CONSELLATED COMM. HOBBE, M.