

COUNTY	LEA	FIELD	Lovington	STATE	NM
OPR	GETTY OIL CO.				MAP
	1 State "PS"				
	Sec. 32, T-16-S, R-37-E				CO-ORD
	660' FSL, 1980' FWL of Sec.				30-025-22244
	Spd 9-13-67				CLASS
	Cmp 10-24-67				Elev
	FORMATION		DATUM		
CSG & SX - TUBING					
8 5/8" 422' 300					
5 1/2" 5200' 2280					
LOGS EL GR RA IND HC A					
	TD 5200', PBD 4800'				
IP SA Perfs 4697-4742' Pmpd 62 BOPD + 2 BW. Pot. Based on 24 hr test.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	B&L Drlg. Co.	PROP DEPTH	5200'	TYPE
DATE				

F.R. 9-14-67; Elev. 3812' DF
PD 5200' - SA
Contr. - B&L Drlg. Co.
10-30-67 AMEND OPERATOR: Formerly TIDEWATER OIL CO.
9-18-67 Drlg. 3436'.
9-25-67 Drlg. 4874'.
10-2-67 TD 5200', MORT
10-9-67 TD 5200', PBD 4800', prep Acid.
Perf @ 4909', 4911', 4916', 4919', 4926',
4938', 4954', 4957', 4962', 4966' W/1 SPI
Acid (4909-66') 3250 gals.
Swbd load & swbd 65 BFW (4909-66')
PB to 4800'

LEA Lovington NM
GETTY OIL CO., #1 State "PS"

Sec. 32-16S-37E

Page #2

10-9-67 Cont.
Perf @ 4697', 4699', 4703', 4705', 4715',
4716', 4739', 4742' W/l SPI
10-16-67 TD 5200', PBD 4800', WO Pmpg equip.
Acid (4697-4742') 2000 gals.
Swbd 30 BLO + 13 BAW in 10 hrs (4697-4742')
10-23-67 TD 5200', PBD 4800', RUP
10-30-67 TD 5200', PBD 4800', COMPLETE
LOG: Anhy 1997', Ystes 3075', SA 4666'.