

CEMENTING	CERTIFICATE
DWL-608-C	

Chell State #1	well in	county, State of Texas, on 11-19				, 19 <u>_67</u>
This work was done for	wrleson & Buff	· · · · · · · · · · · · · · · · · · ·	,	• 3 x 935		
Fidland	(CUSTOMER)	, and covered by		(AD	DRESS)	
(CITY)	(STATE)					
Asserting to Containing to Dec		CASING CEM				
According to Customer's Rep		(TYPE)	stage	tool was set in		_ in. casing c
······································						
1 socks		(TYPE CEMENT	AND PERCENT ADDITIVES)			
Based on information supplied					ising at	ft
in inch drilled						
2 sacks		(TYPE CEMENT	AND PERCENT ADDITIVES)			
sacks						
Based on information supplied						ft
in inch drilled						
3 sacks		(TYPE CEMENT	AND PERCENT ADDITIVES)			
sacks						
based on information supplied						ft.
in inch drilled ho				;		
4 sacks		(TYPE CEMENT	AND PERCENT ADDITIVES)			
sacks						
based on information supplied						ft.
in inch drilled	hole, with			Cemen	t 🗌 was	was not
circulated to ground surface w	vhile cementing produc			·		
This Plug-to Abandon job was	performed under the c	litection supervision and	control of the shows were			
By statement of Customer's R				nea customer.		
2700	9608	- depth using	sacks of cemer	at Dive sat in	845/8	
7550	71,58	depth_using25	sacks of cemer		SAS ARLE C	R PIPE AND SIZE
5700	5608	depth_using	sacks of cemer	5	MES/OLE O	R PIPE AND SIZE
3500	31,63 h to the	depth_using25		U	CALE C	R PIPE AND SIZE
for surface	h to the	depth_using	socks of cemer	Ū.	OPEN HOLE C	R PIPE AND SIZE
			sacks of cemer	nt. Plug set in	OPEN HOLE C	R PIPE AND SIZE
Dowell Representative (		Fellow )				
Dowell Representative		J.L. Stidhan				
Before me this day personally				w	ho by me be	ing duly sworr
upon oath says that the statem Subscribed and sworn before m	1 th	0 C 05		67		
SUDSCRIDED ONG SWORD DEFORE M		day of	1	9		
		,	, <b>,</b>	·		